### **HD 10/21-4 S PLUS**

The HD 10/21-4 S Plus cold water high-pressure cleaner delivers high performance and premium quality. Ergonomic work thanks to Vibrasoft rotary nozzle and EASY!Force Advanced trigger gun.















Order no.

1.286-958.0

- Space-saving upright design
- Air/water-cooled motor
- Energy-saving EASY!Force high-pressure gun for fatigue-free work

Technical data		
EAN code		4054278915487
Current type	Ph / V / Hz	3 / 376 - 424 / 50
Flow Rate	l/h	500 - 1000
Water feed temperature	°C	60
Operating pressure	bar	50 - 210
Max. Pressure	bar	250
Power rating	kW	8
Power cable	m	5
Nozzle size		050
Water feed		1"
Weight (with accessories)	kg	63.9
Weight incl. packaging	kg	73
Dimensions (L × W × H)	mm	607 × 518 × 1063

Equipment		
Trigger gun		EASY!Force Advanced
Trigger gun with soft grip		
High-pressure hose	m	10 / Premium quality / ID 8, 315 bar
Spray lance	mm	1050
Power nozzle		
Dirt Blaster spray lance		
4-pole three-phase motor with air and water cooling		•
Three piston axial pump		with stainless steel pistons
Pressure switch control		•
Integrated fine mesh water filter		
High pressure lance		
Oil sight glass		
Servo Control		
Brass water inlet fitting		
_		

■ Included in delivery.

This device does not require instruction.







- Small footprint and space-saving proportions.
- Easy to manoeuvre and transport.
- Maximum stability ensures a stable footing for the machine.



# 4-pole low-speed motor with air-water cooling system, robust pump with stainless steel pistons and brass cylinder head

- Long service life and low maintenance costs.
- High performance and high efficiency.
- With suction feature and up to 60 °C water temperature.



#### **Ergonomic Vibrasoft Dirt Blaster**

- Reduces vibrations by up to 30%.
- Reduces volume and noise level.
- Rotary nozzle takes the hard work out of extensive cleaning tasks.



























14

		Order no.	Description	
TRIGGER GUNS				
Trigger guns				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.	
Servo Control				
Servo Control, 750 l/h - 1100 l/h	5	4.118-008.0	Water quantity and pressure regulated directly from the hand spray gun.	
SPRAY LANCES				
Rotating spray lances				
Spray lance, 1050 mm, rotatable	6	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	-
LED nozzle light	7	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
Spray lance, 250 mm, rotatable	8	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
Spray lance, 400 mm, rotatable	9	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
Spray lance, 600 mm, rotatable	10	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	11	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	12	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	13	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance extender, 1000 mm	14	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	

 $<sup>\</sup>blacksquare$  Included in delivery.  $\qed$  Available accessories.























				Т
SPRAY LANCES		Order no.	Description	L
Double lance				_
Double lance, 960 mm	15	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance	_	1		+
WC and gutter lance	16	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance	,	•		
Flexible lance, 1050 mm	17	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	18	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner		•		
Gutter cleaning lance	19	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance	•			
Underbody lance	20	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				
Additional handle for EASY!Lock spray lances	21	4.321-380.0	Comfortable in every situation - the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	
ROTARY NOZZLES (DIRT BLASTERS)		'		
Dirt blaster, large				
Dirt blaster Vibrasoft, 050	22	4.114-066.0	Vibrasoft rotary nozzle with rotating point jet for ten times greater cleaning performance. Durable dirt blaster thanks to ceramic nozzle. Reduces vibrations by up to 30% for maximum ergonomics.	•
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°				
Power Nozzle 25°, 050	23	2.113-023.0	Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	
HP nozzle spray angle 0°				
Power nozzle 0°, 055	24	2.113-035.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 15°				
Power nozzle 15°, 055	25	2.113-047.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	
Power nozzle spray angle 40°		1		+
Power Nozzle 40°, 055	26	2.113-055.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
HIGH-PRESSURE HOSES				t
Standard with unions on both sides				Ť
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	27	6.110-031.0	10 m high-pressure hose (M 22 $\times$ 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155 $^{\circ}$ C/315 bar.	•
High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock	28	6.110-041.0		

 $<sup>\</sup>blacksquare$  Included in delivery.  $\hfill\Box$  Available accessories.























		Order no.	Description	
HIGH-PRESSURE HOSES				ľ
Standard with unions on both sides				Ī
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	29	6.110-030.0	15 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	30	6.110-032.0	20 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	_
High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock	31	6.110-014.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock	32	6.110-042.0	15 m high-pressure hose M $22 \times 1.5$ ) with kink protection and threaded couplings at both ends. Further data: DN $10/155^{\circ}$ C/ $220$ bar.	
High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock	33	6.110-043.0	with union on both sides, M 22 $\times$ 1.5 with anti-kink protection. NW 10/155 $^{\circ}$ C/220 bar	
High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock	34	6.110-044.0		
High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock	35	6.110-045.0		
High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock	36	6.110-059.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. $2x M 22 \times 1.5$ with anti-kink protection.	_
High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock	37	6.110-060.0		
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 × EASY!Lock	38	6.110-024.0	1.5 m high-pressure hose (DN 8, M $22 \times 1.5$ ) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M $22 \times 1.5$ ).	
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5	39	6.110-069.0	High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection.	
High-pressure hose Longlife, 10 m, DN 8, 400 bar, 2 × EASY!Lock	40	6.110-038.0	Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressure.	
High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 × EASY!Lock	41	6.110-023.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	42	6.110-027.0	with rotary coupling, 2 × M 22 × 1.5	

 $<sup>\</sup>hfill \square$  Available accessories.

#### **KÄRCHER**

### **EQUIPMENT FOR HD 10/21-4 S PLUS**

### 1.286-958.0

























		Order no.	Description		
HIGH-PRESSURE HOSES					
Longlife 400 with unions on both sides					
High-pressure hose Longlife, 15 m, DN 8, 400 bar, $2 \times EASY!Lock$	43	6.110-029.0	With rotary coupling, $2 \times M$ $22 \times 1.5$		
Food industry version with unions on both side	es				
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock	44	6.110-051.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M $22 \times 1.5$ with anti-kink sleeve.		
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	45	6.110-052.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 × 1.5, with kink protection. NW 8/155°C/250 bar.		
Longlife food industry version with unions on	both s	ides			
High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, 2 $\times$ EASY!Lock	46	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.		
High-pressure hose food grade Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	47	6.110-054.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)		
MULTIPLE-JET NOZZLES					
Triple nozzles					
Triple nozzle, 053	48	4.117-038.0	Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low-pressure flat stream is useful for cleaning agent suction and application.		
Angle vario nozzle 0°-90°					
Angled Vario nozzle, 055	49	4.113-008.0	Variable angle nozzle for spray angle adjustment from $0^{\circ}$ to $90^{\circ}$ . For easy adjustment to all kinds o soiling and surfaces.	f	
NOZZLE UNION / SPACER					
Nozzle union					
Nozzle screws	50	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles		
PIPE CLEANING					
Pipe cleaning hose, ID 6					
Hose assembly TR pipe cleaning DN6 max.2	51	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).		
Pipe cleaning hose, DN 6, 20 m, 220 bar	52	6.110-008.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R $1/8$ nozzle).		
Hose assembly TR pipe cleaning DN6 max.2	53	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).		
Pipe cleaning nozzle					
Dirt blaster pipe cleaning D21/060	54	4.765-002.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted		
Dirt blaster pipe cleaning D30/060	55	4.765-005.0	jets ensure the necessary forward movement, as well as convenient handling.		
Nozzle pipe cleaning size 80	56	5.763-087.0	Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	1	

<sup>☐</sup> Available accessories.

























		Order no.	Description	
PIPE CLEANING	,			
Pipe cleaning nozzle				
Pipe cleaning nozzle	57	5.763-019.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	
	58	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	59	5.763-021.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	60	6.415-440.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
FRV 30	61	2.111-010.0	Surface cleaner with integrated waste water pick-up	
Add-on kit rubber lip	62	2.642-910.0	For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	
Extension hose 5 m	63	4.440-939.0	5m extension hose for FRV 30. Connection sleeve included.	
Add-on kit hose attachment	64	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Add-on kit dirt trap	65	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
Hard surface cleaner FR 30 ME				
FR 30 ME surface cleaner	66	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50				
FR 50 surface cleaner	67	2.111-023.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	g
Machine-specific nozzle kit for FR				
Nozzle kit for FR, 850 l/h - 1100 l/h	68	2.640-442.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Machine-specific nozzle kits for FRV				
Nozzle kit for FRV, 050	69	2.642-433.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
Hard surface cleaner FRV 30 Me				
FRV 30 Me Surface Cleaner	70	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	

<sup>☐</sup> Available accessories.

### **EQUIPMENT FOR HD 10/21-4 S PLUS**

### 1.286-958.0





























71	Order no.	Description	
71	Order no.	Description	L
71			
71			
71			
	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	[
72	2.111-024.0	Surface cleaning with automatic suction of the dirty water for very large surfaces. Hot water cleaning up to 85°C.	
73	4.112-065.0		
74	4.112-069.0		
75	4.112-055.0	For high-pressure cleaners with a flow rate of 900-2500 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
76	5.071-414.0		
77	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
78	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
79	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
80	2.111-019.0	Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.	
	•		
81	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
			Ė
82	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
83	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	[
84	6.645-761.0	Stainless steel injector for cleaning agent and foam applications. Specifically for the HD 10/25-4 S High-pressure cleaner. For precise cleaning agent dosage.	
	73 74 75 76 77 78 80 81 82 83	73 4.112-065.0 74 4.112-069.0 75 4.112-055.0 76 5.071-414.0 77 6.414-050.0  78 2.112-010.0  80 2.111-019.0  81 2.112-013.0  82 4.637-032.0  83 4.637-033.0	cleaning up to 85°C.  73

<sup>☐</sup> Available accessories.



























				_
		Order no.	Description	
MIXERS AND INJECTORS				
Machine-specific nozzle kit with order no. 3.63	7-170	)		
Nozzle insert trapezoidal thread HDS-GER	85	4.769-011.0	For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-001				
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	86	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	87	4.769-001.0	For low pressure with machines up to 1.100 l/h	
QUICK CONNECT				_
Quick-fitting pipe union coupler trapezo	88	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	
Quick-fitting pipe union plug nipple tra	89	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M $22 \times 1.5$ external thread.	
DRUM AND TANK CLEANING		'		
Add-on kit mud sucker	90	2.641-798.0		
OTHER HP ACCESSORIES				
Jet gun	91	2.869-067.0	Short set-up time, easy transport, instant switch off – the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	1 🗆
COUPLING PARTS				
Rotary coupling				
Rotary coupling	92	4.111-021.0	Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	
Connector				
Nozzle connector/screw connector	93	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1 \times M$ 22 $\times$ 1.5 and $1 \times M$ 18 $\times$ 1.5.	
Y distributor	94	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
Short spray unit	95	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles.	ot 🗆
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	96	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	97	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	98	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	

<sup>☐</sup> Available accessories.





























		Order no.	Description	
COUPLING PARTS				
Adapter EASY!Lock				
Adapter M22 - Swivel	99	4.111-032.0	M22 $ imes$ 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	100	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	101	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	102	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	103	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Coupler -2xM22x1,5	104	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \times 1.5 \ m$ .	
ADAPTER for replacement TR22IG-M22AG Er	105	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Automatic, self-winding hose reels				
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\mathrm{m}}$	106	2.639-257.0		
Automatic hose reel, powder-coated steel / plastic, 20 m	107	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	108	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	109	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey-coated, 20 m	110	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	111	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	112	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	

<sup>☐</sup> Available accessories.

#### **KÄRCHER**



























HOSE REELS		Order no.	Description	_	
Automatic, self-winding hose reels					
•	1440	l a caa aa. a		1-	
Powder-coated swivel holder	113	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.		
Stainless steel swivel holder	114	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.		
FACADE AND SOLAR PANEL CLEANING					
Brushes					
Drive for roller brush 500	115	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.		
Splash guard for roller brush 500	116	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.		
Roller brush 500 soft	117	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0), Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.		
Roller brush 500 medium	118	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.		
Roller brush 500 hard	119	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.		
Brush hard	120	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.		
Brush medium	121	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.		
Brush soft	122	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.		
iSolar 800 Advanced	123	6.368-094.0	iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.	o [	
iSolar 400 Advanced	124	6.368-092.0	isolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.		
Telescopic					
TL low pressure adapter	125	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.		
Telescopic lance TL 7 F	126	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.		

 $<sup>\ \</sup>square$  Available accessories.





















		Order no.		
			Description	
FACADE AND SOLAR PANEL CLEANING		<u>'</u>		
Telescopic				
Telescopic lance TL 7 H	127	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. [
Telescopic lance TL 10 H	128	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	129	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	130	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	131	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
Wasserenthärtung		·		
WS 50	132	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.	
WS 100	133	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.	
WS Regenerator	134	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening unit: WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	s C
Hoses	•			
Hose solar	135	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
	136	6.392-977.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
	137	6.392-976.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
Attachment kits and adapters	•			
Case sheet steel	138	6.988-152.0	Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	139	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	140	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	

<sup>☐</sup> Available accessories.

#### **KÄRCHER**

























		Order no.	Description	
WET BLASTING ATTACHMENT				Ė
Nozzle pack for wet blasting attachment				
Nozzle pack TR wet jet set 0050	141	2.112-023.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kårcher wet blasting attachment performance. Only in combination with wet blasting attachment .	[
Boron carbide nozzle				
Boron carbide nozzle, for machines as of 1000 I/h	142	6.415-083.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	[
DRUM AND TANK CLEANING				
Barrel and tank cleaning				
Barrel cleaner BC 14/12	143	2.112-020.0	The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums – in particular oak barrels with a capacity between 225 and 600 liters.	
HKF 50 spray head, brass				
HKF 50 spray head , brass	144	3.631-039.0	Interior cleaning head for barrels and containers with bungholes of 50 mm and more.	
Nozzle kit for HKF 50 spray head (3.631-009.0	/ 3.63	31-039.0)		
Nozzle 045 for dual nozzle operation HKF 50	145	6.415-446.0	Nozzle for dual-nozzle operation	
Nozzle 090 for single nozzle operation HKF 50	146	6.415-447.0	Nozzle for single-nozzle operation	[
Double handle for exact control of the spray head	147	2.863-036.0	Double handle. Precise control of the spray head	
Screw plug for using a spray head with one nozzle	148	5.411-061.0	Screw plug for using a spray head with one nozzle	
WATER CONNECTION				
Geka coupling				
With hose nozzle, R 1"	149	6.388-465.0	with hose barb	[
Hose coupling	150	6.388-458.0	with female thread	
Suction filter				
Water filter	151	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 $\mu$ m mesh, R 3/4" and R 1" connection, without non-return valve	n [
Suction filter with check valve	152	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	[
Fine-mesh water filter				
Add-on kit water filter universal	153	2.637-020.0		[
Fine-mesh water filter with adapter	154	4.730-102.0	Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter 1".	r,

 $<sup>\</sup>hfill \square$  Available accessories.













		Order no.	Description	
WATER CONNECTION				
Fine-mesh water filter				
Fine-mesh water filter, 100 μm, R 1"	155	2.638-270.0	Fine-mesh water filter, $100 \mu m$ , max. temperature $60^{\circ}$ C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$ . Connector 1".	. [
Water supply hose				
Water supply hose	156	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	157	4.440-270.0	NW 19 R1" / R1", up to 85 °C	
WASHING BRUSHES		<u> </u>		
Push-on washing brush				
Push-on wash brush, M $18 \times 1.5$	158	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.	
Rotating washing brush				
Rotating wash brush for > 800 l/h machines, nylon bristles	159	4.113-002.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to $60^{\circ}$ C, M $18 \times 1.5$ (replaceable brush insert).	
Rotating wash brush for > 800 l/h machines, natural bristles	160	4.113-005.0		

 $<sup>\</sup>hfill\square$  Available accessories.