

# HDS 10/21-4 MXA

The hot water high-pressure cleaner with 4-pole, water-cooled electric motor and automatic hose reel skilfully combines user-friendly convenience with maximum performance.





#### 1.071-938.0

- Automatic hose reel including 20 m pressure hose
- Save time and energy: EASY!Force high-pressure gun and EASY!Lock quick-release fasteners
- Robust 3-piston axial pump

Technical data		_
EAN code		4054278955865
Supply voltage	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	500 - 1000
Working pressure	bar / MPa	30 - 210 / 3 - 21
Temperature (for supply 12 °C)	°C	min. 80 - max. 155
Connected load	kW	8
Consumption of heating oil or gas at full load	kg/h	7.3
Consumption of heating oil in eco!efficiency mode	kg/h	5.8
Power cable	m	5
Fuel tank	1	25
Weight (with accessories)	kg	172.6
Weight incl. packaging	kg	184.8
Dimensions (L × W × H)	mm	1330 × 750 × 1210

Equipment		
Cleaning agent function		20 + 10 l tank
Spray gun		EASY!Force Advanced
High-pressure hose	m	20 / ID 8, 315 bar
Spray lance	mm	1050
Power nozzle		•
Integrated automatic hose reel		
ANTI!Twist		
Tanks for cleaning agents, calcification protection and fuel that can be filled from the outside		•
Control panel with display light		•
Pressure switch-off		•
Pole reverse plug (3~)		
2 cleaning agent tanks		•
Dry-running protection		•












Users must receive training on this device.





#### Automatic hose reel

- Scratch-resistant and smooth Ultra Guard HD hose with Teflon<sup>®</sup> coating.
- Automatic hose reel for convenient and safe storage of the 20 metre high-pressure hose.



#### **High efficiency**

- $\bullet$  In ecolefficiency mode, the machine operates in the most economical temperature range (60  $^\circ \rm C)$  with full water flow.
- The burner cycles are optimised to reduce fuel consumption by 20% compared to full load operation.



#### Maximum efficiency

- Highly efficient, tried-and-tested "Made in Germany" burner technology.
- 4-pole electric motor with 3-piston axial pump.
- Water-cooled motor for a high performance and long service life.

## ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0



		Order no.	Description	
TRIGGER GUNS				
Spray guns				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.	
Servo control				
Servo Control, 750 l/h - 1100 l/h	5	4.118-008.0	Water quantity and pressure regulated directly from the hand spray gun.	
Servo Control, 1100 l/h -	6	4.118-009.0		
SPRAY LANCES				
Rotating spray lances				
Spray lance, 1050 mm, rotatable	7	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
LED nozzle light	8	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
Spray lance, 250 mm, rotatable	9	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
Spray lance, 400 mm, rotatable	10	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
Spray lance, 600 mm, rotatable	11	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	12	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	13	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	14	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	

 $\blacksquare$  Included in the scope of supply.  $\hfill\square$  Available accessories.


## **ACCESSORIES FOR HDS 10/21-4 MXA** 1.071-938.0



23-30

22











Order no. Description	
Order no. Description	
SPRAY LANCES	
Rotating spray lances	
Spray lance extender, 1000 mm 15 4.112-048.0 Spray lance extension v	vith EASY!Lock connection. Length 1000 mm.
Double lance	
Double lance, 960 mm     16     2.112-016.0     960 mm double lance for agricultural use (e.g.	or variable pressure adjustment on handle at full water flow rate. Suitable g. stable cleaning).
Angular spray lance	
Spray lance for toilets and rain gutters 17 4.112-029.0 Stainless steel lance WC cleaning of gutters and	and gutter with nozzle insert. Specially shaped for effective and hygienic toilets.
Flexible spray lance	
Flexible lance, 1050 mm 18 4.112-035.0 1050 mm flexible lance areas, e.g. gutters.	with variable bend from 20° to 140°, ideal for cleaning difficult to reach
	:: High-pressure articulated joint with infinite angle adjustment up to 120°. $\hfill\square$ o the spray lance of the pressure washer.
Gutter cleaner	
	leaning of gutter systems. Because of the shape of the lance and the special e cleaned without removing the cover plates.
Undercarriage spray lance	
Underbody lance 21 4.112-032.0 Stainless steel lance for high-pressure nozzle.	effective and easy underbody and wheel arch cleaning. Without
Additional handle	
new EASY!Lock generat the particular task. Regu	tuation – the additional handle is easy to attach to the spray lance of our ion and makes work easier by allowing you to adjust your posture to suit ularly changing your posture relieves the strain on your body, making work to the 360°-rotatable spray lance, the additional handle can simply be fully for greater flexibility.
KÄRCHER POWER NOZZLE	
Power nozzle spray angle 25°	
Power nozzle 25°, 052         23         2.113-024.0         Fan jet nozzle with 25°	spray angle, suitable for large areas and removing stubborn dirt and stains. $lacksquare$
Power nozzle , 070 24 2.113-028.0 Fan jet nozzle for large-	area coverage and stubborn dirt and stains.
HP nozzle spray angle 0°	
Power nozzle 0°, 050 25 2.113-034.0 High-pressure nozzle w	ith powerful jet for extremely stubborn dirt.
Power nozzle 0°, 075 26 2.113-037.0	
Power nozzle spray angle 15°	
Power nozzle 15°, 055         27         2.113-047.0         Fan jet nozzle with 15°	spray angle suitable for stubborn dirt.
Power nozzle 15°, 070         28         2.113-049.0	

 $\blacksquare$  Included in the scope of supply.  $\Box$  Available accessories.

### ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0



				Т
		Order no.	Description	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 40°				
Power nozzle 40°, 050	29	2.113-054.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
Power nozzle 40°, 075	30	2.113-056.0		
HIGH-PRESSURE HOSES				
Ultra Guard				
High-pressure hose Ultra Guard, 20 m, DN 8, max. 315 bar	31	6.110-083.0	Ultra Guard high-pressure hose with smooth and extremely hard-wearing coating. Robust hose line for maximum service life in the toughest conditions.	:
Standard with unions on both sides				
High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock	32	6.110-041.0	Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	33	6.110-031.0	High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANTI!Twist and 10 m long.	
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	34	6.110-030.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	35	6.110-032.0	20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar.	
High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock	36	6.110-014.0	Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANTI!Twist for pressures up to 315 bar.	
High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock	37	6.110-042.0	Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar 15 m long high-pressure hose (DN 10).	:
High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock	38	6.110-043.0	20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	
High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock	39	6.110-044.0	Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock	40	6.110-045.0	40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar.	۱C
High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock	41	6.110-059.0	Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock	42	6.110-060.0	With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	

■ Included in the scope of supply. □ Available accessories.

## ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0

54

53



56

55

		Order no.	Description	
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 × EASY!Lock	43	6.110-024.0	1.5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure.	
High-pressure hose Longlife, 10 m, DN 8, 400 bar, 2 × EASY!Lock	44	6.110-038.0	Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANTI!Twist. Approved for 400 bar pressure.	
High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 × EASY!Lock	45	6.110-023.0	Robust high-pressure hose with double steel core, ANTI!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, for up to 400 bar pressure.	
High-pressure hose Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	46	6.110-027.0	High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	
High-pressure hose Longlife, 15 m, DN 8, 400 bar, 2 × EASY!Lock	47	6.110-029.0	The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar.	
Food industry version with unions on both sid	es		•	
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock	48	6.110-051.0	High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With quick and robust EASY!Lock hand screw connection at both ends.	
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	49	6.110-052.0	Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, ANTI!Twist and EASY!Lock hand screw connections.	
Longlife food design with screw connections a	t both	ends		
High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, 2 × EASY!Lock	50	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.	
Special hoses			•	
High-pressure hose curved, 1.5 m, DN 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5	51	6.110-068.0	For connection to hose reels: high-pressure hose, with M 22 $\times$ 1.5 connection and curved EASY!Loch hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure.	< 🗆
WEED CONTROL				
WR 50	52	2.114-013.0	In combination with a hot water high-pressure cleaner from Kårcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	
WR 20	53	2.114-014.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	
WR 100	54	2.114-015.0	Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners.	
WR 10	55	2.114-016.0	In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	
ECO!BOOSTER				
eco!Booster TR 080	56	2.113-089.0	eco!Booster with 50% higher area performance than the Kärcher power nozzle; ideal for delicate surfaces. For cold and hot water high-pressure cleaners (nozzle size 080).	

□ Available accessories.

52

## **ACCESSORIES FOR HDS 10/21-4 MXA** 1.071-938.0













67-68



		Order no.	Description	
QUICK CONNECT				
Quick coupling	57	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Karcher spray unit, suitable for trigger gun/spray lance interface. With M 22 $\times$ 1.5 internal thread.	
Male coupling	58	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 $\times$ 1.5 external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	59	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	
OTHER HP ACCESSORIES				
Jet gun	60	2.869-067.0	Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	I
FLUE PIPE				
Flue gas adapter	61	4.656-149.0	Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for	Τ
	62	4.656-080.0	connection to a stack system).	ľ
Exhaust gas nozzle	63	4.656-079.0	Exhaust gas nozzle (oval connection, diameter 157 mm) for connection to the hot water high-pressure cleaner. With draught diverter for flue tube connection. For flue tube diameter up to 200 mm.	
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large				_
Dirt blaster, large, 050	64	4.114-027.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzl	e
Dirt blaster, large, 070/080	65	4.114-030.0	and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	ľ
MULTIPLE-JET NOZZLES				ſ
Angled vario nozzle 0-90°				-
Angled Vario nozzle, 055	66	4.113-008.0	Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds o soiling and surfaces.	f
STEAM JET NOZZLE / NOZZLE PROTEC	TOR / ROLLOVI	ER NOZZLE		
Steam jet nozzles				
Steam jet nozzle 50°	67	4.116-000.0	Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.	
	68	4.116-001.0	50° flat jet for cleaning and thawing operations in steam mode, e.g. thawing sand and gravel, de-icing formwork, dewaxing vehicles.	
Steam jet nozzle 40°, 070	69	2.114-006.0	Brass steam nozzle for operation of the HDS in steam stage.	1
Steam jet nozzle 40°, 110	70	2.114-012.0		

### ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0











	1			
		Order no.	Description	
NOZZLE UNION / SPACER				
Nozzle union				
Nozzle screws	71	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	72	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	73	6.110-008.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	74	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle				
Pipe cleaning dirt blaster D21/060	75	4.765-002.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Pipe cleaning dirt blaster D21/090	76	4.765-003.0	jets ensure the necessary forward movement, as well as convenient handling.	
Pipe cleaning dirt blaster D30/060	77	4.765-005.0		
Pipe cleaning dirt blaster D30/090	78	4.765-010.0		
Pipe cleaning nozzle 080	79	5.763-087.0	Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle 100	80	5.763-088.0		
Pipe cleaning nozzle	81	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	
	82	5.763-019.0	environmentally-friendly cleaning of blocked drains and pipes.	
	83	5.763-016.0		
	84	5.763-020.0		

### **ACCESSORIES FOR HDS 10/21-4 MXA** 1.071-938.0

85-86       87         87       87         95       96	8	8	$\left  \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	
		Order no.	Description	_
PIPE CLEANING Pipe cleaning nozzle				_
Pipe cleaning nozzle	85	5.763-017.0	the pipe. (R 1/8" connection, 3 × 30° backwards, diameter 30 mm.)	
	86	J.703-021.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Hose fastening attachment kit	87	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Dirt trap attachment kit	88	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
FR 30 Me surface cleaner				
Hard Surface Cleaner FR 30 Me	89	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50		1		
Surface Cleaner FR 50 Me	90	2.111-023.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	
Machine-specific nozzle kits for FR				
Nozzle kit for FR, 850 l/h - 1100 l/h	91	2.640-442.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Nozzle kit for FR, 1100 l/h - 1300 l/h	92	2.639-188.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h).	
Machine-specific nozzle kits for FRV				
Nozzle kit for FRV, 050	93	2.642-433.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
Nozzle kit for FRV, 080	94	2.642-982.0	Ī	
FRV 30 Me surface cleaner				
FRV 30 Me Surface Cleaner	95	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
Extension hose FRV 30 Me and FRV 50 Me	96	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	
Surface Cleaner FR 50 Me				
FRV 50 Me surface cleaner	97	2.111-024.0	Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the [FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C.	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Advanced 3, 900 l/h - 2500 l/h	98	4.112-065.0	Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced [ 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher.	
Available accessories.				

## ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0



		Order no.	Description	
FOAM SYSTEMS			· ·	
Cup foam lance				
Cup foam lance DUO Advanced 3, 900 I/h - 2500 I/h	99	4.112-069.0	DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank.	[
Cup foam lance Basic 3, 900 l/h - 2500 l/h	100	4.112-055.0	High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality.	[
1-litre cleaning agent container for cup foam lance basic	101	5.071-414.0	For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	
1-litre cleaning agent container for cup foam lance advanced	102	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Kit				
Inno Foam Set with detergent injector	103	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or	
Inno Foam Set	104	2.112-008.0	disinfection.	E
Easy Foam Set				
Easy Foam Set with RM injector	105	2.112-010.0	0.0 HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine	
Easy Foam Set	106	2.112-011.0	specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set		•		
Nozzle kit 090 for Inno / Easy Set 700-1,000 I/h	107	2.111-019.0	Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 I/h. For optimal foam system performance.	
Nozzle kit 110 for Inno / Easy Set 1,000-1,300 l/h	108	2.111-020.0	Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance.	
Foam nozzle mounting kit				
Foam nozzle attachment kit	109	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS				
Cleaning agent injector				
Cleaning agent injector for high and low pressure (without nozzles)	110	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Cleaning agent injector for high pressure (without nozzle)	111	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with order no. 4.63	37-033	3.0	1	-
Nozzle kit 750-1000 l/h	112	4.769-011.0	For HD/HDS 750 – 1000 l/h. Consists of nozzle insert + HP power nozzle + union	Тг

#### рсне

### **ACCESSORIES FOR HDS 10/21-4 MXA** 1.071-938.0




















118











### ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0

127 128 128 128 128			$\left  \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	
		Order no.	Description	
COUPLING PARTS		order no.		
EASY!Lock adapter				
Adapter 6 TR22IG-M22AG	127	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	128	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	129	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Adapter hose extension 9 TR	130	4.111-037.0	Adapter 9 to connect the new hose with the new hose	
Adapter 12 rotary coupling EASY!Lock 22 IG - M22 × 1.8 AG	131	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Automatic, self-winding hose reels for wall mo	untin	5		
Automatic plastic hose reel incl. high-pressure hose, 15 m	132	2.639-257.0	Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	
Automatic hose reel, powder-coated steel / plastic, 20 m	133	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	134	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	135	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey-coated, 20 m	136	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	137	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	138	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Zinc-coated swivel holder	139	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	140	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	

## ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0

		43		
	1	50	151-152 IS3-154	
		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reel attachment	kit			
Attachment kit automatic hose reel HDS M/S	141	2.110-011.0	Automatic hose reel as a complete attachment kit that's easy to mount. Suitable for HDS medium and super class. For maximum convenience when winding and unwinding the high-pressure hose.	
Attachment kit automatic hose reel holder HDS M/S	142	2.110-020.0	Holder includes connection material for installing an automatic hose reel to machines in the HDS Middle and Super classes.	
FACADE AND SOLAR PANEL CLEANING				
Brushes	1	1		
Drive for roller brush 500	143		Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	144	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roller brush 500 soft	145	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
Roller brush 500 medium	146	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roller brush 500 hard	147	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	148	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
Brush medium	149	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
Brush soft	150	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
iSolar 800 Advanced	151	6.368-094.0	iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.	
iSolar 800 Advanced (1100-1300 l/h)	152	6.368-095.0	For water flow rates of 1,100-1,300 l/h: The 800-mm iSolar water-driven brush head with two contra-rotating disc brushes and flexible angle joint ensures that photovoltaic systems are given an even clean.	
iSolar 400 Advanced	153	6.368-092.0	iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.	
	154	6.368-093.0	The iSolar 400 water-driven disc brush (working width 400 mm) is designed for water flow rates of 1,100-1,300 l/h. For small to medium-sized photovoltaic systems (including elevated systems).	

## ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0



		Order no.	Description	
FACADE AND SOLAR PANEL CLEANIN	G			
Telescopic lances				
TL low pressure adapter	155	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	156	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	157	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	:. 🗆
Telescopic lance TL 10 H	158	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	159	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	160	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	161	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
Water softening				
WS 50	162	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	
WS 100	163	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	
WS Regenerator	164	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening unit: WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	s 🗆
Hoses				
iSolar HP hose 7	165	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 10	166	6.392-977.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 14	167	6.392-976.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
Attachment kits and adapters				
iSolar fall protection	168	6.988-152.0	Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.	

## ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0

181



182-183

Т





176





		Order no.	Description					
WET BLASTING ATTACHMENT								
Wet blasting attachment (without nozzle)								
Wet blasting attachment with flow control (without nozzles)	169	4.115-000.0	Paint, rust and scale removal made easy: Kārcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.					
Wet blasting attachment without flow control (nozzles not included)	170	4.115-006.0	Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling. Assembly on spray lance instead of high-pressure nozzle. Without water flow regulation					
Nozzle kits for wet jet unit								
Nozzle kit for wet jet unit 055	171	2.112-024.0						
Nozzle kit for wet jet unit 070	172	2.112-027.0	4.115-000.0   4.115-006.0.					
Boron carbide nozzle								
Boron carbide nozzle, for machines up to 1,000 l/h	173	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.					
Boron carbide, for machines from 1,000 l/h	174	6.415-083.0						
DRUM AND TANK CLEANING								
Barrel and tank cleaning								
Barrel cleaner BC 14/12	175	2.112-020.0	The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels – especially oak barrels with a capacity of between 225 and 600 litres.					
HKF 50 spray head, brass		•						
HKF 50 M spray head	176	3.631-039.0	Constant rotational speed and lightweight design: The compact interior cleaning head for cleaning vats and tanks with openings of 50 mm or wider.					
Nozzle kit for spray head HKF 50 (3.631-009.0 / 3.631-039.0)								
Nozzle 045 for 2-nozzle operation HKF 50	177	6.415-446.0	Nozzle for dual-nozzle operation					
High-pressure full jet nozzle 090 for interior cleaning heads	178	6.415-447.0	High-pressure full jet nozzle 090 for interior cleaning heads with a spray angle of 0°, made of hardened stainless steel and with 1/8-inch thread.					
Double grip for precise control of spray head	179	2.863-036.0	Double handle. Precise control of the spray head					
1/8" screw plug for interior cleaning heads	180	5.411-061.0	Screw plug for high-pressure interior cleaning heads with 1/8-inch thread.					
ADD ON KITS								
Flame monitoring attachment kit								
Flame monitoring attachment kit for HDS Middle and Super Class	181	2.641-796.0	More safety thanks to ABS HDS M/S flame monitoring system: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes.					
WATER CONNECTION								
Geka coupling								
Geka connector with hose barb, R 3/4"	182	6.388-455.0	with hose liner					

□ Available accessories.

180

### ACCESSORIES FOR HDS 10/21-4 MXA 1.071-938.0


















Available accessories.

natural bristles