KARCHER

KÄRCHER CENTER TRAFALGAR






Product Data Sheet BRC 45/45 C

Deep and interim carpet cleaning in one machine.

The BRC 45/45 C offers two functions in one machine. As well as giving superb deep cleaning results in a single pass, the 45/45 can be used for interim two-stage cleaning, providing fast, efficient cleaning of carpets, with very short drying times. Using Kärcher's iCapsol detergent, medium-large area carpets can be cleaned and ready for vacuuming within 20 minutes.



- Two 40cm contra-rotating brushes agitate carpets for a thorough clean.
- iCapsol interim cleaning process has the carpet ready for traffic in 20 minutes.
- Floating brush system provides consistent brush contact, even on uneven surfaces.
- Fast brush change as no tools are required.
- Float switch in the wastewater tank protects the vacuum motor.
- Removable dirty water tank with built-in handle, for simple emptying of wastewater.
- Optional hose and hand tool for spot cleaning and upholstery cleaning.
- Fresh water tank with integrated 1.5m filling hose.
- Large 10" non marking tyres provide simple transportation.
- Easy operations makes it ideal for training personnel.





Range Comparison

Kärcher Interim Carpet Cleaner



Accessories

Standard accessories



Fast Drying Carpet Cleaner RM 768

Encapsulation detergent for interim cleaning

- . For use with the BRS 43/500 C
- · Very low moisture
- · Encapsulates dirt particles and brings them to the surface, ready to be vacuumed with dry vacuum cleaner
- · Leaves carpets dry enough to be vacuumed and reused after only 20
- · Can dramatically reduce the need for deep cleaning pH 6 in concentrate

Processing

Dilute just 6% detergent to 94% water. Apply with BRS 43/500 C interim carpet deaning machine.

Economy

50ml is usually enough to cover 1m2. One 10 litre container is enough to cover over 200m2

Order no: 6.295-278 (10 litre)





Technical Specification

Part Number	1.008-056
Dimensions (L x W x H) (mm)	768 x 546 x 1245
Weight (kg)	75.3
Cable length (m)	15
Tank capacity dirty/clean (f)	45/38
Brush rotation speed (front/rear) (rpm)	1050/874
Suction width (mm)	458
Working width (mm)	408
Max. practical performance (m ² /h)	350/1000
Power supply (PtvV/Hz)	1/240/50



Unit C, Foundry Close Horsham West Sussex **RH135TX United Kingdom** 0845 611 8012 www.trafalgarcleaningequipment.co.uk Unit C Foundry Close Horsham West Sussex RH13 5TX United Kingdom

T. 01403 273444

E. sales@tce.org.uk

W. trafalgarequipment.co.uk

